




SCHOCH EDELSTAHL



T-Stück DIN 2615

mit gleichem Abzweig



S = nahtlos / seamless

W = geschweis / welded

Abmessung	S	W	L	Kg/Stück
D x s			mm	
17,2 x 2,30	▪		40	0,06
21,3 x 2,00	▪	▪	50	0,09
x 2,60	▪		50	0,1
x 2,90	▪		50	0,11
26,9 x 2,00	▪	▪	58	0,12
x 2,60	▪		58	0,16
x 2,90	▪		58	0,18
33,7 x 2,00	▪	▪	76	0,19
x 2,60	▪		76	0,25
x 2,90	▪		76	0,29
x 3,60	▪		76	0,35
42,4 x 2,00	▪	▪	96	0,32
x 2,60	▪		96	0,41
x 2,90	▪		96	0,46
x 3,60	▪		96	0,57

Abmessung	S	W	L	Kg/Stück
D x s			mm	
48,3 x 2,00	▪	▪	114	0,46
x 2,60	▪		114	0,58
x 2,90	▪		114	0,65
x 3,00		▪	114	0,69
x 3,60	▪		114	0,79
60,3 x 2,00	▪	▪	128	0,57
x 2,90	▪		128	0,83
x 3,00		▪	128	0,86
x 4,00	▪		128	1,12
76,1 x 2,60	▪		152	1,04
x 2,90	▪		152	1,25
x 3,00		▪	152	1,29
x 5,60	▪		152	2,3
88,9 x 2,60		▪	172	1,45
x 3,00		▪	172	1,7

Abmessung	S	W	L	Kg/Stück
D x s			mm	
88,9 x 3,20	▪		172	1,85
x 5,60	▪		172	3,1
114,3 x 2,60		▪	210	2,25
x 3,00		▪	210	2,67
x 3,60	▪		210	3,1
x 6,30	▪		210	5,3
139,7 x 3,00		▪	248	4,4
x 4,00	▪		248	4,8
168,3 x 3,00		▪	286	6
x 4,50	▪		286	7,25
219,1 x 4,00		▪	356	12,7
x 6,30	▪		356	20,7
273,0 x 3,00		▪	432	11
323,9 x 4,00		▪	508	20,4

lösungsgeglüht u. gebeizt, ab 3,0 mm mit Fase gem. DIN 2559/22

Verfügbare Werkstoffe:

- 1.4541
- 1.4571

Tel.: 07831/9357-0

info@schoch-edelstahl.de
www.schoch-edelstahl.de

Edel sei der Stahl...
...und komplett von SCHOCH!

